



# DUO-SAFETY LADDER CORPORATION



## Solid Beam Aluminum Ladders

These incorporate Duo-Safety's exclusive tongue and groove arrangement. This outstanding construction design holds the sections firmly and rigidly, without brackets, hooks or obstructions of any kind. These compact ladders require a minimum of banking space - and have the extra advantage of being especially stable and rigid.

### Series 1000-A

2 3/4" Channel Rail  
750 lb Duty Rated

#### SPECIFICATIONS

##### SERIES 1000-A 2-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
10'	7' 2.25"	18.5"	4.56"	29#
12'	8' 2.25"	18.5"	4.56"	32#
14'	9' 2.25"	18.5"	4.56"	34#
16'*	9' 11.5"	18.5"	4.56"	40#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

***Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.***

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

\*Only the 16' length has a pulley and 3/8" manila rope installed  
All other lengths are raised manually