



DUO-SAFETY LADDER CORPORATION

Solid Beam Aluminum Ladders

These incorporate Duo-Safety's exclusive tongue and groove arrangement. This outstanding construction design holds the sections firmly and rigidly, without brackets, hooks or obstructions of any kind. These compact ladders require a minimum of banking space - and have the extra advantage of being especially stable and rigid.

Series 900-A Series 925-A

3 1/4" Channel Rail
750 lb Duty Rated

SPECIFICATIONS

SERIES 900-A 2-SECTION				
Size	Closed Length	Width	Banking Thickness	Weight
20'	12' 2.75"	21.75"	5.375"	60#
24'	14' 2.75"	21.75"	5.375"	72#
SERIES 925-A 3-SECTION				
Size	Closed Length	Width	Banking Thickness	Weight
22'	10' 8.75"	24"	7.625"	82#
26'	11' 8.75"	24"	7.625"	92#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.



Model 900A



Model 925A